



### Prevents Cracks from becoming Potholes

KOLD FLO is a modified asphalt emulsion crack filler designed for maintenance of asphalt and concrete pavements. It is ideal for roads, highways, parking lots, and driveways.

UNIQUE developed KOLD FLO as a cost-effective repair solution that prevents cracks from becoming potholes by sealing them from the weather's destructive freeze and thaw cycles.

### Ready to Use Saving You Time and Money

KOLD FLO requires no heating or special preparation, and is ready to use right out of the container. Repair crews save time by being able to grab and go without waiting for the material to be ready for application.

Since no heat preparation is required, you save money by not having to waste material. The safety and portability of KOLD FLO make it the crack filler of choice.

### How Does your Crack Filler Compare to KOLD FLO®

- › **Minimal Preparation:** No waiting for kettles to heat up. Crews can be ready to go in minutes.
- › **Easy Application:** You can apply KOLD FLO right from its original container with a pour pot or drum pump.
- › **Safe to Apply:** Since no heating is required, you avoid the dangerous burns that can occur from hot-applied material.
- › **Reduced Traffic Delays:** When properly applied, KOLD FLO can be driven over within 30 minutes without tracking.

*KOLD FLO is a convenient material for filling cracks without needing any special equipment or training.*

KOLD FLO® is a product of  **unique®**



### 1

#### Prepare the Area

Clean out debris from the cracks so that the KOLD FLO can completely fill the damaged area.

For best results, either sweep area with a broom or blow out the debris.

### 2

#### Apply KOLD FLO®

Using the one-gallon bottle, a pour pot or a drum pump, pour KOLD FLO into the crack  $\frac{3}{4}$  of the length.

Allow a few minutes for KOLD FLO to seep completely down into the crack.

### 3

#### Complete the Repair

Push KOLD FLO into the crack, with a "U" shaped squeegee, allowing the excess to fill the remaining  $\frac{1}{4}$  of the crack.

For cracks deeper than 2", a second application of KOLD FLO may be needed.

### KOLD FLO Coverage (per gallon)

1/4" (6MM) WIDE X 1/4" (6MM) DEEP = 300 LINEAR FEET (92 LINEAR METERS)

1/2" (13MM) WIDE X 1/2" (13MM) DEEP = 75 LINEAR FEET (23 LINEAR METERS)

1" (25MM) WIDE X 1" (25MM) DEEP = 25 LINEAR FEET (8 LINEAR METERS)

KOLD FLO is available in 55-gallon drums, 5-gallon pails and 1-gallon easy pour bottles.

*Call UNIQUE today to learn more about how KOLD FLO works in preventing cracks from becoming potholes!*

KOLD FLO® is a product of  **unique®**



PLEASE RECYCLE

PRINTED ON RECYCLED STOCK  
WITH SOY BASED INKS.