



## Data Sheet – MICROMIX® Mini Cold Mix

### Product Description

MICROMIX® mini cold mix is an easy and ready to use high performance cold applied asphalt sand mix repair material.

### Recommended Uses

Use **MICROMIX** mini mix to fix smaller and shallower repair areas such as eroding concrete expansion joints, shallow pavement “pop outs” and other narrow and shallow applications.

### Benefits / Features

- Reduces total repair costs
- Use from featheredge to 6”
- Easily repairs smaller areas
- Immediate traffic access
- Seals out water
- Compatible with the thermal expansion of concrete
- Quick & easy repair

### Limitations

**MICROMIX** mini mix is designed for installation with tack coat and should be installed above 50F. Once installed, performance will meet or exceed the surrounding material.

### Surface Determination

Why has the pavement failed? Is there presence of salt, freezing damage, drainage water, deteriorated control or expansion joints? The surface area to be repaired should be in solid condition.

### Surface Preparation

The quality and durability of your repair depends on the surface to be patched. Remove loose concrete, asphalt and other dirt and debris.

### Packaging

Item #	Description	
92-00010	MICROMIX® Mini Cold Mix Tube 10#	5-10# tubes per box 180 - 10# tubes per stretch wrapped pallet 4140 - 10# tubes per truckload
92-00011	MICROMIX® Mini Cold Mix Bag 50#	56 - 50# bags per stretch wrapped pallet 896 - 50# bag per truckload

Truckload quantities are typical but may vary depending on destination, truck tare weight and/or trailer type (box van, flat bed, rail shipments or ocean freight container).

Another Quality Product Available From  
 UNIQUE Paving Materials Corp.  
 3993 East 93<sup>rd</sup> Street Cleveland, OH 44105  
 800-441-4880  
[www.uniquepavingmaterials.com](http://www.uniquepavingmaterials.com)

### Mixing

No mixing is required.

### Placement

Apply a tack coat using UNIQUE’s KOLD-FLO® crack filler or other suitable asphalt emulsion crack filler liberally to the repair area. Allow the tack coat to cure slightly (usually 5 minutes) and start to turn black in color.

Open the bag and shovel or trowel the **MICROMIX** mini mix into the repair area leaving it crowned ½” or so above the existing pavement.

Compact the **MICROMIX** mini mix with a hand tamper or other suitable compaction method.

Sprinkle sand, cement powder or road dirt to minimize tracking and accelerate setup.

For questions, please contact UNIQUE’s Technical Department.

### Coverage

10# of **MICROMIX** mini mix covers approximately 0.5 square foot, 2” deep.

### Shelf Life

One year if stored in an unopened bag at room temperature.

### Freight

Class 55





**Caution:**

This product contains petroleum derived and various chemicals to enhance performance. Refer to SDS for details. Avoid skin contact and use appropriate safety equipment, suggested but not limited to approved safety glasses and gloves. In case of contact with eyes, immediately flush with water for at least 15 minutes and seek medical attention. DO NOT TAKE INTERNALLY. Keep out of reach of children. Avoid prolonged contact with clothing. Avoid hazards by following all precautions found in the Safety Data Sheet. Please read this information prior to using product.

**Limited Warranty:**

UNIQUE Paving Materials Corporation (UNIQUE) warrants that at the time and place we make shipment our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED. WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OR TRADE OR OTHERWISE ARE SPECIFICALLY DISCLAIMED. As the exclusive remedy for breach of this warranty, we will replace defective materials, provided, however, that the buyer examines the material when received and promptly notifies us in writing of any defect before the materials are used or incorporated into structure. Three (3) months after UNIQUE has shipped the materials, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefor terminates, and no action for breach of any duties may thereafter be commenced. UNIQUE shall in no event be liable for consequential damages. No warranty is made with respect to materials not manufactured by UNIQUE.

MICROMIX® is a registered trademark of UNIQUE Paving Materials Corp.

Another Quality Product Available From  
UNIQUE Paving Materials Corp.  
3993 East 93<sup>rd</sup> Street Cleveland, OH 44105  
800-441-4880  
[www.uniquepavingmaterials.com](http://www.uniquepavingmaterials.com)

