

UNIQUE®
**ASPHALT
RESURFACER**

Data Sheet-

UNIQUE® Asphalt Resurfacer

Product Description

UNIQUE® Asphalt Resurfacer is a Gilsonite modified asphalt resurfacer designed to rejuvenate and seal aged asphalt pavements and protect them against water, moisture, and deicing salts.

Recommended Uses

Use to seal over alligator cracking in asphalt pavements to protect asphalt surfaces from water damage caused by freeze/thaw cycles, stains from dirt, deicing salts, oil, and other contaminants. Use on any aged asphalt surface, including driveways and parking lots. Extend your pavement's service life using KOLD-FLO® Crack Filler for cracks and finish with a top coat of **UNIQUE** Asphalt Resurfacer. Your aging asphalt can be restored to nearly new condition.

Benefits / Features

- Signature grade Gilsonite modified asphalt emulsion based formula
- UV Protection
- Passes FAA P-625 Fuel Resistance Test
- Coal tar free
- Polymer modified
- Professional grade
- Repairs alligator cracking in asphalt pavements
- Stable for easy mixing
- Excellent adhesion to pavement surfaces
- Environmentally friendly, water-based formulation

Limitations

UNIQUE asphalt resurfacer should not be applied when the ambient temperature is expected to drop below 50°F or rain is expected within 24 hours following application. Do not use a sealer brush to apply asphalt resurfacer without immediately squeegeeing off all excess material. Do not use this product over coal tar sealed pavement without the use of **UNIQUE**'s remediation product.

Surface Preparation

Ruts, divots, depressed areas, and total asphalt failures must be repaired before applying **UNIQUE** asphalt

resurfacer. The surface must be clean and free of all loose material, dirt, oil, grease, and other contaminants to ensure bond. Call **UNIQUE**'s Technical Department for questions related to on-site optimizations.

Mixing

Some separation/settling may occur over time. Stir/mix well **UNIQUE** asphalt resurfacer to achieve a consistent mixture.

Placement

Surface should be Saturated Surface Dry (SSD) and free of any standing water. Resurfacer can be applied directly from the container or with automated spray equipment and finished with a squeegee removing all excess material from the pavement's surface.

Curing

Initial cure time before opening to foot traffic should be 4-6 hours. Final cure time before opening to vehicle traffic should be 24-48 hours. Cure time will vary due to ambient conditions. Night applications will take longer than daylight applications.

Durability

UNIQUE asphalt resurfacer is modified with Gilsonite, a naturally occurring solid asphalt, and combined with other high-performance surfactant additives has demonstrated superior performance relative to other asphalt-based resurfacers. Like other **UNIQUE** products, it is expected to outperform competitive products.

Storage

Keep from freezing.

Shelf Life

Twelve months in unopened containers.

Color

Brown liquid that dries black.

Coverage

One gallon of **UNIQUE** asphalt resurfacer will cover approximately 100 square feet (11 square yards). The coverage rate will vary due to age, surface condition, and porosity. (See coverage chart, next page.)

Another Quality Product Available From **UNIQUE**
3993 East 93rd Street Cleveland, OH 44105
800-441-4880
www.uniquepavingmaterials.com

UNIQUE
PAVEMENT
PRESERVATION
SOLUTIONS

UNIQUE®
**ASPHALT
 RESURFACER**

COVERAGE RATE GUIDE for UNIQUE® ASPHALT RESURFACER				
gal/100 ft ²	ft ² /gal	gal/ft ²	yd ² /gal	gal/yd ²
1.7	60.0	0.017	6.7	0.15
1.6	64.3	0.016	7.1	0.14
1.4	69.2	0.014	7.7	0.13
1.3	75.0	0.013	8.3	0.12
1.2	81.8	0.012	9.1	0.11
1.1	90.0	0.011	10.0	0.10
1.0	100	0.010	11.1	0.09
0.9	112.5	0.009	12.5	0.08
0.8	128.6	0.008	14.3	0.07
0.7	150.0	0.007	16.7	0.06
0.6	180.0	0.006	20.0	0.05

Packaging

Item #	Description	
51-00002	UNIQUE® Asphalt Resurfacer Pail 1-gal (8.42#)	120 (8.42) pails per stretch-wrapped pallet 3,360 (8.42#) pails per truckload
51-00003	UNIQUE® Asphalt Resurfacer Pail 5-gal (40#)	36 (40#) pails per stretch-wrapped pallet 1,008 (40#) pails per truckload
51-00004	UNIQUE® Asphalt Resurfacer Drum 55-gal (440#)	4 (440#) drums per stretch-wrapped pallet 84 (440#) drums per truckload (with pallets) 91 (440#) drums per truckload (no pallets)
51-00005	UNIQUE® Asphalt Resurfacer Tote 275-gal (2,200#)	1 (2,200#) tote per pallet 20 (2,200#) totes per truckload
51-00006	UNIQUE® Asphalt Resurfacer Tote 330-gal (2,640#)	1 (2,640#) tote per pallet 16 (2,640#) totes per truckload

Truckload quantities are typical but may vary depending on destination, truck tare weight and/or trailer type (box van, flatbed, rail shipments, or ocean freight container).

Another Quality Product Available From UNIQUE
 3993 East 93rd Street Cleveland, OH 44105
 800-441-4880
www.uniquepavingmaterials.com



UNIQUE®
ASPHALT
RESURFACER

Caution:

This product contains petroleum-derived and various chemicals to enhance performance. Refer to SDS for details. Avoid skin contact and use appropriate safety equipment, suggested but not limited to approved safety glasses and gloves. In case of contact with eyes, immediately flush with water for at least 15 minutes and seek medical attention. **DO NOT TAKE INTERNALLY.** Keep out of reach of children. Avoid prolonged contact with clothing. Avoid hazards by following all precautions found in the Safety Data Sheet. Please read this information prior to using product.

Warranty:

Unique Paving Materials Corp. (UNIQUE) warrants that at the time and place we make shipment our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OR TRADE OR OTHERWISE. As the exclusive remedy for breach of this warranty, we will replace defective materials, provided, however, that the buyer examines the material when received and promptly notifies us in writing of any defect before the materials are used or incorporated into structure. Three (3) months after UNIQUE has shipped the materials, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any duties may thereafter commence. UNIQUE shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by UNIQUE. We cannot warrant or in any way guarantee any particular method of use of application or the performance of materials under any particular condition. Neither this warranty nor our liability may be extended or amended by our salespeople, distributor or representatives or by any sales information or drawings.

UNIQUE is a registered trademark of UNIQUE Paving Materials Corp.

Another Quality Product Available From UNIQUE
3993 East 93rd Street Cleveland, OH 44105
800-441-4880
www.uniquepavingmaterials.com

UNIQUE®
PAVEMENT
PRESERVATION
SOLUTIONS