

UNIQUE® CONCRETE POURABLE CRACK FILLER

Data Sheet – UNIQUE® Concrete Crack Filler Concrete Crack Filler

Product Description

UNIQUE® Pourable Concrete Crack Filler is a Gilsonite modified asphalt emulsion concrete crack filler designed for filling cracks and joints in concrete pavements. **UNIQUE** concrete crack filler is formulated with special polymers and additives to seal out water, protect, and preserve concrete pavements.

Recommended Uses

Use **UNIQUE** concrete crack filler to fill cracks and joints on any concrete surface, including driveways and parking lots. **UNIQUE** concrete crack filler should be applied to cracks from hairline to 1" wide. Use other **UNIQUE** Pavement Preservation and repair products for larger crack and joint repairs.

Benefits / Features

- Signature grade Gilsonite modified asphalt emulsion based formula
- Asphalt-based and free of coal tar
- Can be applied to damp pavement
- Cost-effective
- Minimum preparation required
- Safe and easy to apply
- Excellent adhesion to pavement surfaces
- Excellent cold weather flexibility
- Reduced traffic delays
- Environmentally friendly

Limitations

UNIQUE concrete crack filler should not be applied when the ambient temperature is expected to drop below 50°F or rain is expected within 24 hours following application.

Mixing

Some separation/settling may occur over time. Stir **UNIQUE** pourable concrete crack filler to achieve a consistent mixture.

Surface Preparation

The surface must be clean and free of all loose material and dirt. Clean out debris from the cracks so the **UNIQUE** concrete crack filler can completely fill the damaged area.

Another Quality Product Available From **UNIQUE**
3993 East 93rd Street Cleveland, OH 44105
800-441-4880
www.uniquepavingmaterials.com

Area to be repaired should be in sound condition. Be sure no undermining of the pavement base has occurred. Undermining can be severe and require backfilling before any application of **UNIQUE** concrete crack filler. If there is the presence of undermining, fill the crack partly with clean sand or backer rod. **UNIQUE** concrete crack filler fills from bottom to top.

Placement

The surface should be dry or slightly damp and free of any standing water. **UNIQUE** concrete crack filler can be applied directly from the container or with automated applicator equipment. Multiple coats may be applied for deeper and undermined areas. If the crack filler continues to sink in undermined areas of the crack, add additional clean sand and additional crack filler. For a smoother finish, pour or pump **UNIQUE** concrete crack filler into the crack $\frac{3}{4}$ of the length. Allow a few minutes for the concrete crack filler to seep completely down into the crack. Push the concrete crack filler into the remaining crack length using a "U" or "V" shaped squeegee. Multiple coats may be applied for deeper and undermined areas. If **UNIQUE** concrete crack filler continues to sink in undermined areas of the crack, add additional clean sand and additional **UNIQUE** crack filler. Allow 2-4 hours curing time between coats.

Coverage

One gallon of **UNIQUE** pourable concrete crack filler will cover approximately:

WIDTH	x	DEPTH	LINEAR FEET	LINEAR METERS
1/4" (6MM)	x	1/4" (6MM)	300	92
1/2" (13MM)	x	1/2" (13MM)	75	23
1" (25MM)	x	1" (25MM)	25	8

Clean up

Water-soluble before drying. Clean container and tools before material drying.

Color

Gray

UNIQUE®
PAVEMENT
PRESERVATION
SOLUTIONS

UNIQUE® CONCRETE POURABLE CRACK FILLER

Curing

When properly applied, **UNIQUE** concrete crack filler can be driven over within 30 minutes without tracking. Cure time will vary due to ambient conditions.

Storage

Keep from freezing.

Shelf Life

Six months in unopened containers.

Packaging

Item #	Description	
63-00003	UNIQUE® Concrete Crack Filler Bottle 1-quart (2#)	720 (2#) bottles (pkg 4 /box) per stretch-wrapped pallet 18,720 (2#) bottles per truckload
63-00002	UNIQUE® Concrete Crack Filler Bottle 1-gal (8#)	144 (8#) bottles (pkg 4 /box) per stretch-wrapped pallet 4,032 (8#) bottles per truckload
63-00005	UNIQUE® Concrete Crack Filler Pail 5-gal (38#)	36 (38#) pails per stretch-wrapped pallet 1,008 (38#) pails per truckload
63-00004	UNIQUE® Concrete Crack Filler Drum 55-gal (440#)	4 (440#) drums per stretch-wrapped pallet 88 (440#) drums per truckload (with pallets) 96 (440#) drums per truckload (no pallets)

Truckload quantities are typical but may vary depending on destination, truck tare weight and/or trailer type (box van, flatbed, rail shipments, or ocean freight container).

Caution:

This product contains petroleum-derived and various chemicals to enhance performance. Refer to SDS for details.

Limited Warranty:

UNIQUE Paving Materials Corporation (UNIQUE) warrants that at the time and place we make shipment our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED. WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OR TRADE OR OTHERWISE ARE SPECIFICALLY DISCLAIMED. As the exclusive remedy for breach of this warranty, we will replace defective materials, provided, however, that the buyer examines the material when received and promptly notifies us in writing of any defect before the materials are used or incorporated into structure. Three (3) months after UNIQUE has shipped the materials, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefor terminates, and no action for breach of any duties may thereafter be commenced. UNIQUE shall in no event be liable for consequential damages. No warranty is made with respect to materials not manufactured by UNIQUE.

UNIQUE® is a registered trademark of UNIQUE Paving Materials Corp.

Another Quality Product Available From UNIQUE
3993 East 93rd Street Cleveland, OH 44105
800-441-4880
www.uniquepavingmaterials.com

